



TECKSOFT 2000 CROSS-SECTIONS

A wide variety of additional profiles are available. Custom profiles can rapidly be designed to meet specifications.




SQUARE

H (in mm)	W (in mm)	PART NUMBER
.118 (3.0)	.118 (3.0)	27-100
.195 (5.0)	.195 (5.0)	27-103
.250 (6.4)	.250 (6.4)	27-101
.375 (9.5)	.375 (9.5)	27-104
.500 (12.7)	.500 (12.7)	27-102
.670 (17.0)	.670 (17.0)	27-106



D-SHAPE

H (in mm)	W (in mm)	PART NUMBER
.060 (1.5)	.150 (3.8)	27-201
.090 (2.3)	.090 (2.3)	27-206
.120 (3.0)	.150 (3.8)	27-203
.120 (3.0)	.250 (6.4)	27-207
.120 (3.0)	.360 (9.1)	27-208
.125 (3.2)	.090 (2.3)	27-209
.140 (3.6)	.250 (5.4)	27-202
.250 (6.4)	.375 (9.5)	27-204
.375 (9.5)	.500 (12.7)	27-200
.500 (12.7)	.500 (12.7)	27-212
.700 (17.8)	.500 (12.7)	27-213




I/O OR FLAT

H (in mm)	W (in mm)	PART NUMBER
.060 (1.5)	.750 (19.0)	27-302
.060 (1.5)	.900 (22.9)	27-304
.060 (1.5)	1.625 (41.0)	27-306
.062 (1.6)	2.000 (50.8)	27-301
.080 (2.0)	.830 (21.1)	27-307




C-FOLD

H (in mm)	W (in mm)	X 1	X 2	PART NUMBER
.395 (10.0)	.430 (10.9)	.080 (2.0)	.125 (3.2)	27-402
.400 (10.2)	.430 (10.9)	.040 (1.0)	.125 (3.2)	27-400
.470 (11.9)	.487 (12.4)	.110 (2.8)	.110 (2.8)	27-403
.675 (17.1)	.580 (14.7)	.156 (4.0)	.165 (4.2)	27-405
.675 (17.1)	.590 (15.0)	.156 (4.0)	.165 (4.2)	27-401



KNIFE EDGE

H (in mm)	W (in mm)	PART NUMBER
.106 (2.7)	.445 (11.3)	27-501
.250 (6.4)	.750 (19.1)	27-500



CLIP

H (in mm)	W (in mm)	PART NUMBER
.125 (3.2)	.250 (6.4)	27-601

RECTANGLE

H (in mm)	W (in mm)	PART NUMBER
.040 (1.0)	.120(3.0)	27-709
.040 (1.0)	.157(4.0)	27-710
.040 (1.0)	.200(5.1)	27-701
.040 (1.0)	.275(7.0)	27-711
.040 (1.0)	.395(10.0)	27-712
.040 (1.0)	.510(13.0)	27-713
.062 (1.6)	.200(5.1)	27-708
.062 (1.6)	.300(7.6)	27-714
.080 (2.0)	.160(4.1)	27-715
.080 (2.0)	.275(7.0)	27-716
.080 (2.0)	.400(10.2)	27-717
.100 (2.5)	.265(6.7)	27-718
.100 (2.5)	.375(9.5)	27-719
.120 (3.0)	.155(3.9)	27-720
.125 (3.2)	.250(6.4)	27-721
.125 (3.2)	.500(12.7)	27-705
.130 (3.3)	.190(4.8)	27-723
.130 (3.3)	.380(9.7)	27-724
.150 (3.8)	.500(12.7)	27-725
.157 (4.0)	.315(8.0)	27-726
.157 (4.0)	.591(15.0)	27-727
.160 (4.1)	.200(5.1)	27-728
.196 (5.0)	.315(8.0)	27-707
.250 (6.4)	.375(9.5)	27-706
.250 (6.4)	.500(12.7)	27-730
.276 (7.0)	.433(11.0)	27-731
.295 (7.5)	.591(15.0)	27-732
.375 (9.5)	.500(12.7)	27-733
.710 (18.0)	.827(21.0)	27-703

ORDERING INFORMATION

Pressure sensitive adhesive mounting strips are standard. Consult the factory for custom profiles, other attachment methods or reeled parts. Contact your Tecknit representative for design assistance.

27-

M

Attachment:
PSA = 0
No PSA = 1

Core:
0 = No Foam
1 = TPE Foam: Std
3 = TPE Foam: FR-L
5 = Urethane Foam FR-L
6 = TPE Foam: Urethane
7 = TPE Foam: FR-H
9 = TPA Foam: FR-H

Length:
(M - designates
the length in
metric units (mm).
Ex: 255mm = M0025

Gasket Profile
Designator:
1XX = Square
2XX = D Shape
3XX = I/O or Flat
4XX = C-Fold
5XX = Knife Edge
6XX = Clip
7XX = Rectangle

Fabric:
1 = Ni/Cu PET Taffeta
3 = Ni/Cu Nylon Non-Woven
5 = Ni/Cu Nylon Ripstop FR
6 = Nickel Mesh Fabric
7 = Ni/Cu PET Non-Woven
8 = Copper Nylon Ripstop

Tecknit Europe Limited, Swingbridge Road, Grantham, England. NG31 7XT

Tel: 44 (0)1476 590600 Fax: 44 (0) 1476 591600 e-mail: tecknit.sales@twp-europe.co.uk web: www.twp-europe.co.uk